

Gages for Printed Boards

KFRS

- Gage Factor Approx. 2.0
- Applicable Linear Expansion Coefficient 13
- Self-temperature-compensation Range -30 to 120°C

Applicable Adhesives and Operating Temperature Ranges

CC-33A: -196 to 120°C
PC-6: -196 to 150°C

■ Foil Strain Gages for Printed Boards















Printed boards are used for varieties of products including cellular phones, car navigation systems and digital cameras. To evaluate the mechanical and thermal characteristics of these printed boards, the KFRS gages were developed by integrating the advantageous features of KFG and KFR gages.

- Ultra-small gage bases enable bonding of these gages to components mounted on a printed board and narrow spaces on the printed board. The gage base of the uni-axial model is 1.2mm long by 1.1mm wide; that of biaxial and triaxial model is 2.5 mm².
- The linear expansion coefficient is $13 \times 10^{-6}/^{\circ}\text{C}$ that is applicable to component-mounted PC boards.
- The self-temperature compensation range is widened to -30 to 120°C to meet heat cycle tests.















■ Types, lengths and codes of leadwire cables pre-attached to KFRS gages

Type	2 polyester-coated copper wires		3 polyester-coated copper wires		Vinyl-coated flat 2-wire cable		Vinyl-coated flat 3-wire cable		Middle-temperature 2-wire cable	Middle-temperature 3-wire cable
	C1, D34, D35		C1		D34, D35		C1		D34, D35	
Length	C1, D34, D35		C1		D34, D35		C1		D34, D35	
10 cm	N10C2	N10C3								
30	N30C2	N30C3								
1 m			L1M2R	L1M2S	L1M3R	L1M3S	R1M2	R1M3		
3			L3M2R	L3M2S	L3M3R	L3M3S	R3M2	R3M3		
5			L5M2R	L5M2S	L5M3R	L5M3S	R5M2	R5M3		
Oprg. temp. range	-196 to 150°C		-10 to 80°C				-100 to 150°C			
Remarks			L-6		L-7		L-11		L-12	

KFRS Gages ● Uniaxial 120Ω

Pattern	Leadwire Cable – Type and Shape	Operating Temp. Range	Leadwire Length	Model
KFRS-1-120-C1-13  5 times enlarged view Uniaxial ● Base Size 4 x 1.4 mm ● Gage Length 1 mm ● Gage Resistance 120Ω ● Pieces per Pack 10	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFRS-1-120-C1-13 L1M3R
			3m	KFRS-1-120-C1-13 L3M3R
			5m	KFRS-1-120-C1-13 L5M3R
	Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFRS-1-120-C1-13 L1M2R
			3m	KFRS-1-120-C1-13 L3M2R
			5m	KFRS-1-120-C1-13 L5M2R
	Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFRS-1-120-C1-13 R1M3
			3m	KFRS-1-120-C1-13 R3M3
			5m	KFRS-1-120-C1-13 R5M3
	Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFRS-1-120-C1-13 R1M2
			3m	KFRS-1-120-C1-13 R3M2
			5m	KFRS-1-120-C1-13 R5M2
	3 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-1-120-C1-13 N10C3
			30cm	KFRS-1-120-C1-13 N30C3
	2 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-1-120-C1-13 N10C2
	30cm		KFRS-1-120-C1-13 N30C2	
KFRS-02-120-C1-13  10 times enlarged view Uniaxial ● Base Size 1.2 x 1.1 mm ● Gage Length 0.2 mm ● Gage Resistance 120Ω ● Pieces per Pack 10	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-C1-13 L1M3R
			3m	KFRS-02-120-C1-13 L3M3R
			5m	KFRS-02-120-C1-13 L5M3R
	Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-C1-13 L1M2R
			3m	KFRS-02-120-C1-13 L3M2R
			5m	KFRS-02-120-C1-13 L5M2R
	Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFRS-02-120-C1-13 R1M3
			3m	KFRS-02-120-C1-13 R3M3
			5m	KFRS-02-120-C1-13 R5M3
	Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFRS-02-120-C1-13 R1M2
			3m	KFRS-02-120-C1-13 R3M2
			5m	KFRS-02-120-C1-13 R5M2
	3 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-C1-13 N10C3
			30cm	KFRS-02-120-C1-13 N30C3
	2 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-C1-13 N10C2
	30cm		KFRS-02-120-C1-13 N30C2	

KFRS Gages ● Biaxial 120Ω/Triaxial 120Ω

Pattern	Leadwire Cable – Type and Shape	Operating Temp. Range	Leadwire Length	Model
KFRS-02-120-D34-13  5 times enlarged view Biaxial, 0°/90° ● Base Size 2.5 x 2.5 mm ● Gage Length 0.2 mm ● Gage Resistance 120Ω ● Pieces per Pack 5	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-D34-13 L1M3S
			3m	KFRS-02-120-D34-13 L3M3S
			5m	KFRS-02-120-D34-13 L5M3S
	Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-D34-13 L1M2S
			3m	KFRS-02-120-D34-13 L3M2S
			5m	KFRS-02-120-D34-13 L5M2S
	Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFRS-02-120-D34-13 R1M3
			3m	KFRS-02-120-D34-13 R3M3
			5m	KFRS-02-120-D34-13 R5M3
	Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFRS-02-120-D34-13 R1M2
			3m	KFRS-02-120-D34-13 R3M2
			5m	KFRS-02-120-D34-13 R5M2
3 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-D34-13 N10C3	
		30cm	KFRS-02-120-D34-13 N30C3	
2 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-D34-13 N10C2	
		30cm	KFRS-02-120-D34-13 N30C2	
KFRS-02-120-D35-13  10 times enlarged view Triaxial, 0°/90°/45° ● Base Size 2.5 x 2.5 mm ● Gage Length 0.2 mm ● Gage Resistance 120Ω ● Pieces per Pack 5	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-D35-13 L1M3S
			3m	KFRS-02-120-D35-13 L3M3S
			5m	KFRS-02-120-D35-13 L5M3S
	Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFRS-02-120-D35-13 L1M2S
			3m	KFRS-02-120-D35-13 L3M2S
			5m	KFRS-02-120-D35-13 L5M2S
	Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFRS-02-120-D35-13 R1M3
			3m	KFRS-02-120-D35-13 R3M3
			5m	KFRS-02-120-D35-13 R5M3
	Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFRS-02-120-D35-13 R1M2
			3m	KFRS-02-120-D35-13 R3M2
			5m	KFRS-02-120-D35-13 R5M2
3 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-D35-13 N10C3	
		30cm	KFRS-02-120-D35-13 N30C3	
2 polyester-coated copper wires	-196 to 150°C	10cm	KFRS-02-120-D35-13 N10C2	
		30cm	KFRS-02-120-D35-13 N30C2	